



**slat** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
3000K warmweiß  
L70/50.000 h

dimmbar

**Installation:**  
2 x Kabeleinführung;  
Anschlussklemme  
3 x 2,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Sicherheitsglas satiniert

**Schutzart:**  
IP65

**EEK:**  
A

light technology:  
230V Power LED  
3000K warm white  
L70/50.000 h


dimmable

installation:  
2 x cable entry point;  
connection terminal  
3 x 2,5 mm<sup>2</sup>

material:  
aluminium die-casting  
powder-coated  
safety glass satined

protection class:  
IP65

EEC:  
A



Größe in mm  
size in mm

Art.-Nr. item no.	Farbe colour	Systemleistung system performance	Lichtrichtung light direction
91130-AN	anthracite RAL 7016	16 W/685 lm	
91130-CB	cool brown	16 W/685 lm	
91130-SG	space grey	16 W/685 lm	
91130-WH	pure white RAL 9016	16 W/685 lm	
91130-BL	deep black RAL 9005	16 W/685 lm	

IP44.de outside lighting  
Mühlenstraße 20 . 33378 Rheda-Wiedenbrück . Germany  
T +49 5242 5797-0 . F +49 5242 5797-10  
welcome@IP44.de . www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.  
IP44.de reserves the right to product adaptations at any time, without prior notice.